

Strip Length	Belt Thickness	Pitch	Order No.	kg
--------------	----------------	-------	-----------	----

Belt Fastener D70-C		Connecting Pin Dia. 1.0 mm		
Special Steel		Minimum Pulley Diameter 20 mm		

300 mm	up to 1.5 mm	4 mm	42 101 70 30	0.1
600 mm	up to 1.5 mm	4 mm	42 101 70 60	0.3
1200 mm	up to 1.5 mm	4 mm	42 101 70 12	0.6

Splice with or without Lacing Tool

Belt Fastener D71-C		Connecting Pin Dia. 1.4 mm		
Special Steel		Minimum Pulley Diameter 25 mm		

300 mm	1.5 - 2.0 mm	4 mm	42 101 71 30	0.2
600 mm	1.5 - 2.0 mm	4 mm	42 101 71 60	0.5
1200 mm	1.5 - 2.0 mm	4 mm	42 101 71 12	1.0



Belt Fastener D72-C		Connecting Pin Dia. 1. mm		
Special Steel		Minimum Pulley Diameter 35 mm		

300 mm	2.0 - 2.5 mm	4 mm	42 101 72 30	0.3
600 mm	2.0 - 2.5 mm	4 mm	42 101 72 60	0.5
1200 mm	2.0 - 2.5 mm	4 mm	42 101 72 12	1.1

Material : Special Steel

Box content:
4 Complete Sets

Belt Fastener D73-C		Connecting Pin Dia. 1.4 mm		
Special Steel		Minimum Pulley Diameter 50 mm		

300 mm	2.5 - 3.5 mm	4 mm	42 101 73 30	0.3
600 mm	2.5 - 3.5 mm	4 mm	42 101 73 60	0.6
1200 mm	2.5 - 3.5 mm	4 mm	42 101 73 12	1.2

Note:
Hammer Fastener D70, D71, D72, D73 can be spliced with the Lacing Tool MATOROLL or a Vice Lacer MATOVICE (see pages 48-49)

Belt Fastener D70-SS		Connecting Pin Dia. 1.0 mm		
Stainless Steel 1.4404		Minimum Pulley Diameter 20 mm		

300 mm	up to 1.5 mm	4 mm	42 104 70 30	0.1
600 mm	up to 1.5 mm	4 mm	42 104 70 60	0.3
1200 mm	up to 1.5 mm	4 mm	42 104 70 12	0.6

Splice with or without Lacing Tool

Belt Fastener D71-SS		Connecting Pin Dia. 1.4 mm		
Stainless Steel 1.4404		Minimum Pulley Diameter 25 mm		

300 mm	1.5 - 2.0 mm	4 mm	42 104 71 30	0.2
600 mm	1.5 - 2.0 mm	4 mm	42 104 71 60	0.5
1200 mm	1.5 - 2.0 mm	4 mm	42 104 71 12	1.0



Belt Fastener D72-SS		Connecting Pin Dia. 1.4 mm		
Stainless Steel 1.4404		Minimum Pulley Diameter 35 mm		

300 mm	2.0 - 2.5 mm	4 mm	42 104 72 30	0.3
600 mm	2.0 - 2.5 mm	4 mm	42 104 72 60	0.5
1200 mm	2.0 - 2.5 mm	4 mm	42 104 72 12	1.1

Material : Stainless Steel

Box content:
4 Complete Sets
(8 Fastener Strips + 4 Connecting Pins)

Belt Fastener D73-SS		Connecting Pin Dia. 1.4 mm		
Stainless Steel 1.4404		Minimum Pulley Diameter 50 mm		

300 mm	2.5 - 3.5 mm	4 mm	42 104 73 30	0.3
600 mm	2.5 - 3.5 mm	4 mm	42 104 73 60	0.6
1200 mm	2.5 - 3.5 mm	4 mm	42 104 73 12	1.2

Note:
Hammer Fastener D70, D71, D72, D73 can be spliced with the Lacing Tool MATOROLL or a Vice Lacer MATOVICE (see pages 48-49)

Strip Length	Belt Thickness	Pitch	Order No.	kg
Belt Fastener D82-C				
Special Steel		Connecting Pin Dia. 1.4 mm Minimum Pulley Diameter 60 mm		
300 mm	3.0 - 4.0 mm	6 mm	42 101 82 30	0.4
Belt Fastener D83-C				
Special Steel		Connecting Pin Dia. 2.1 mm Minimum Pulley Diameter 75 mm		
300 mm	4.0 - 5.0 mm	8 mm	42 101 83 30	0.5
Belt Fastener D84-C				
Special Steel		Connecting Pin Dia. 2.1 mm Minimum Pulley Diameter 100 mm		
300 mm	5.0 - 6.5 mm	8 mm	42 101 84 30	0.6
Belt Fastener D85-C				
Special Steel		Connecting Pin Dia. 2.1 mm Minimum Pulley Diameter 125 mm		
300 mm	6.5 - 7.5 mm	8 mm	42 101 85 30	0.7
Belt Fastener D86-C				
Special Steel		Connecting Pin Dia. 3.0 mm Minimum Pulley Diameter 175 mm		
300 mm	7.5 - 8.5 mm	10 mm	42 101 86 30	1.0
Belt Fastener D87-C				
Special Steel		Connecting Pin Dia. 3.0 mm Minimum Pulley Diameter 225 mm		
300 mm	8.5 - 9.5 mm	12 mm	42 101 87 30	1.2
Belt Fastener D88-C				
Special Steel		Connecting Pin Dia. 3.5 mm Minimum Pulley Diameter 300 mm		
300 mm	9.5 - 11 mm	16 mm	42 101 88 30	1.8
Belt Fastener D89-C				
Special Steel		Connecting Pin Dia. 3.5 mm Minimum Pulley Diameter 350 mm		
300 mm	11 - 12.5 mm	16 mm	42 101 89 30	2.1

Splice without Lacing Tool



Material : Special Steel

Box content:
4 Complete Sets
(8 Fastener Strips + 4 Connecting Pins)